

DRYER DATA SHEET Refrigerant Dryers

| MODEL DATA | | | | | | |
|------------|-------------------------------------|--------------|-------------|-------------------|--|--|
| 1 | Manufacturer | ZEKS | | | | |
| 2 | Date | 12/29/16 | | | | |
| 3 | Model Number | 800NCEA400 | | | | |
| 4 | Cycling/Non-Cycling | NON-CYCLING | | | | |
| 5 | Refrigerant Type | R-404A | | | | |
| | DESCRIPTION | FULL FLOW | 10% FLOW | UNITS | | |
| 6 | Tested Flow | 800 | 80 | scfm ^b | | |
| 7 | Outlet Pressure Dewpoint | 40.5 | 40.5 | °F | | |
| 8 | Pressure Drop | 3.2 | 0.9 | psi(d) | | |
| 9 | Total Dryer Input Power | 5.9 | 5.7 | kW | | |
| 10 | Specific Package Power ^c | .73 | 7.15 | kW/100 scfm | | |

Notes:

a. Dryer ratings at the following inlet conditions to the dryer (as per ISO 7183, Table 2, Option A2):

| • | Inlet Compressed Air Temperature: | 100°F (38°C) |
|---|--|------------------|
| ٠ | Inlet Compressed Air Pressure: | 100 psig (7 Bar) |
| ٠ | Max. Ambient Air Temperature: | 100°F (38°C) |
| ٠ | Inlet Compressed Air Relative Humidity | 100% (Saturated) |

- b. SCFM defined as the volume of free air in cubic feet per minute measured at 14.5 psia (1.0 Bar), 68°F (20°C) temperature and 0% R.H. (0 WVP).
- c. (Total Dryer Input Power/tested flow) x 100



This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.

Consult the CAGI website, <u>www.cagi.org</u>, for a list of participants in the third party verification program.